

CV-MR421S CV-MR421N

4CH 1080P Mobile DVR



- H.264 high performance video compression.
- GPS/G-Sensor Logging and event triggering.
- Support 3G/4G/Wi-Fi router via Ethernet (CV-MR421N).
- Build in backup power (Option).
- Record rate 30fps/1080P.
- 4CH Full HD (Downward compatible),4CH Sound input.
- Storage: Up to 256GB*2 SD card (SDXC).
- Anti-vibration design.
- Trigger Output 12V.
- Support power output to cameras.
- Trigger the image: CH1~CH3.
- Ignition - off record.
- Wide range DC 8V~36V power input.
- Surge protection design.
- Windows AP: including Playback, e-map, G-sensor information, print, and search functions.

Specifications

Model	CV-MR421S	CV-MR421N
System	AHD / TVi / NTSC / PAL	
Video / Audio Input	4CH	
Video out	RCA x1	
Audio out	RCA x1	
S/N Ratio	>40dB	
Screen display	1 / 2 / 3 / 4	
Live Resolution	NTSC:720(H) x 480(V) ; PAL :720(H) x 576(V)	
Recording Resolution	D1: 702x480(NTSC); 702x576(PAL), 960H/ 720P/ 1080P	
Recording Frame Rate	D1: 30fps per Channel(NTSC) / 25fps per Channel(PAL) 960H/720P/1080P: 30pfs/ 25fps	
Recording Quality	Low/ Middle/ High	
Recording Mode	Automatically overwrite	
Multi-task	Live / Record / Play	Live / Record / Play / Network
Di Input /DC 12V Out	Di X3 / DC 12V X1	
External indicator light	Optional	
USB	USB2.0 X2	
Storage	SDXC SD X2 up to 512GB	
Language	English/ Chinese	
Monitor	N/A	3G / 4G Mobile phone (iPhone / iPad / Window Mobile / Android)
IR remote control	Standard	
GPS	G-Mouse Type, supports protocol: NMEA 0183	
G Sensor	3 Axis G-force sensor	
Ethernet	N/A	RJ45 Ethernet 10/100M
Browse the way	N/A	Remote software VMS (64CH)
Network Protocol	N/A	DHCP/HTTP/TCP/IP/SMTP/RTP/RSTP
Remote control	N/A	Monitor / Playback / Backup /DVR control/ GPS/ Map
Anti-vibration	ISO16750-3	
Shock-proof	Yes	
Power	DC 8~36V	
Operating Temperature	-10 to +60°C (w/o SD card)	
Operating Humidity	Less than 90%	
Dimension	135(W) x 40(H) x 135(D)mm	

